

三久大型通風式乾燥機

SUNCUE VENTILATING GRAIN DRYER



SKS-580CG Direct



SKS-580BB Indirect

Applications:

Agricultural Products	Corn, Peanut, all kinds of seeds, Chili, Bean, Garlic, Coffee bean, Cassava, Sesame, Rapeseed, Paddy, Wheat
Foodstuff	Walnut, Longan, Sunflower seeds, Dry shallot, Garlic chip, Dry tofu
Herb	Fructus Lycii, Gerdenia, Herbs, Radish
Others	Bambo chopsticks, Wooden products, Animal feeds, Duck feather, Goose feather

Features :

1.Low drying cost :

Attachable to SUNCUE biomass furnace. Free from using fossil oil. Energy conservation and CO₂ reduction.

2.Flexibility :

Multi sizes drying chambers are available to suit different grain types.

3.Easy Control :



Digital temperature controller to control desired hot air temperature. User friendly.

4.Most Convenience :

Using timer to control required drying time. Dryer will stop when drying time is up.

5.High durability & efficiency :

Large area of heat exchanger of indirect heating way is made of stainless steel.

Specifications					
Model					
Item		SKS - 580 ML (Low heat type)	SKS - 580 MH (High heat type)	SKS - 580 CG	SKS - 580 C
Heating way		Direct			Indirect
Dimension(mm) (Lx WxH)		5077x2458x1740		8745x2458x1875	8820x2458x2267
Net weight (kg) approx.		Single layer :655 Double layer:760		Single layer :1140 Double layer:1310	Single layer :1420 Double layer:1590
Burner	Type	Gun type, Single nozzle High pressure, Spray burner		Gun type, Double nozzle High pressure, Spray burner	
	Ignition	High-pressure automatic ignition			
	Max. Combustion (liter/hour)	5.6	7.8	23	28
	Temperature increase range	+10°C~ 28°C	+10°C~ 40°C	+10°C~ 60°C	
	Fuel type	Kerosene or Premium Diesel			
Electricity		1P/3P,220V/380V,60Hz		3P, 220V/ 380V, 60Hz	
Total horse power kW(HP)		1P:1.17(1.5) 3P:1.55(2)		4.75 (6 1/3)	
Drying bin	Double layer	9.10 m ³ (8.76 m ²)		18.19 m ³ (17.52m ²)	
	Single layer	3.76 m ³ (8.76 m ²)		7.52 m ³ (17.52m ²)	
Application	Double layer	Big grain : such as Longan, peanut, garlic bulb, corn with cob (for seed)			Suitable to dry food that requires indirect drying, such as herbs, dry shallot, garlic chip, dry tofu.
	Single layer	Small grain : such as Paddy, maize, wheat, sesame, rapeseed, vegetable seed, coffee bean.			
Safety device		Thermo-over relay, Air pressure switch, Timer, Burner flame sensor, Control fuse, Overheat sensor			Thermo-over relay, Air pressure switch, Timer,Control fuse

• Specifications and color subject to change without prior notice.

SUNCUE®

SUNCUE COMPANY LTD.

No.396, Minsheng Rd., Wufeng Dist., Taichung City 413, Taiwan (R.O.C.)
 TEL:+886-4-2339-7171 FAX:+886-4-2330-2939
 www.suncue.com E-mail:suncue@ms10.hinet.net

AGENT